

# NetCommander 8-Port Cat5 KVM Switch 1U Rack-Mount

MODEL NUMBER: **B072-008-1**



## Features

- Expandable - Cascade a second level of KVM switches to control up to 128 servers from a single station
- Extend distance: between computer and switch up to 30 meters/100 ft.
- Rack mountable: sleek, 1U space saving KVM switches
- Innovative CAT5 technology: eliminate cable clutter at the rack
- Multi-layer security: protects your corporate data
- Easy server management: choice of On Screen Display, Hot-key, or push button control
- Multi-platform: PS/2 and USB support
- To convert DisplayPort or HDMI computers to VGA, use adapters P134-06N-VGA-V2 or P131-06N. Maximum video resolutions using adapters may vary.
- Add Model B021-000-17 for space saving, in-the-rack, LCD, Keyboard and Mouse
- Compact Size: 17"W x 5"D x 1.75"H
- Video Resolution: 1600x1200@75Hz
- Internal Power Supply
- Compatible with all major operating systems
- Constructed of heavy-duty steel housing
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Note: B051-000 remote access IP unit is not compatible with our B072-008-1 or B072-016-1 1U Rack-Mount NetCommander Cat5 KVM Switch Series.

## Highlights

- 8 RJ45 Ports utilize inexpensive Cat5 patch cables
- Expandable - Cascade a second level of KVM switches to control up to 128 servers from a single station
- Compatible with all major operating systems
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

## System Requirements

- Computers: The B078-101-USB-1 Server Interface Module must be used to connect a server to the server ports on the KVM switch.
- For computers with DisplayPort or HDMI, change to VGA using adapters P134-06N-VGA-V2 or P131-06N. Maximum video resolutions using adapters may vary.
- Compatible with all major operating systems

## Package Includes

- 8-Port NetCommander 1U Rackmount Cat5 KVM Switch
- 6-ft. (1.83 m) Power Cord
- 6-ft. (1.83 m) Firmware Upgrade Cable
- Rackmount Bracket kit

## Specifications

| OVERVIEW |              |
|----------|--------------|
| UPC Code | 037332127532 |
| Console  | No           |



Powering Business Worldwide



|                                              |                                                     |
|----------------------------------------------|-----------------------------------------------------|
| Max CPU                                      | 128                                                 |
| Technology                                   | Cat5/5e; PS/2; VGA/SVGA                             |
| <b>VIDEO</b>                                 |                                                     |
| Max Supported Video Resolution               | 1600 X 1200 @75 Hz                                  |
| Max. Distance (Between any 2 Units)          | 100 ft (30.5m)                                      |
| Max Number of Ports (Entire Chain)           | 128                                                 |
| <b>INPUT</b>                                 |                                                     |
| Voltage Compatibility (VAC)                  | 100; 110; 120; 127; 200; 208; 220; 230; 240         |
| Input Frequency                              | 50/60Hz                                             |
| Input Current                                | 120V (0.7A) / 230V (0.3A)                           |
| Power Input Receptacle                       | IEC-320-C14                                         |
| <b>POWER</b>                                 |                                                     |
| Power Consumption (Watts)                    | 8.00                                                |
| <b>CONNECTIONS</b>                           |                                                     |
| Number of Ports                              | 8                                                   |
| PC/Server Connections                        | VGA; USB; PS/2                                      |
| Side A - Connector 1                         | (8) RJ45 (FEMALE)                                   |
| Side A - Connector 2                         | (1) RJ11 (FEMALE)                                   |
| Side B - Connector 1                         | (1) HD15 (FEMALE)                                   |
| Side B - Connector 2                         | (2) MINI DIN-6 (FEMALE)                             |
| Computer Keyboard and Mouse Interface        | PS/2; USB                                           |
| Computer Monitor Interface                   | VGA                                                 |
| Console Keyboard and Mouse Interface         | PS/2                                                |
| Console Monitor Interface                    | VGA                                                 |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b> |                                                     |
| LED Indicators                               | Green(CPU ON, SELECTED)                             |
| <b>PHYSICAL</b>                              |                                                     |
| Color                                        | Black                                               |
| Material of Construction                     | Steel (Steel, Electrogalvanized, Cold Rolled, Coil) |
| Rackmountable                                | Yes                                                 |
| Shipping Dimensions (hwd / in.)              | 4.40 x 7.40 x 20.00                                 |



Powering Business Worldwide



|                                      |                                                                                 |
|--------------------------------------|---------------------------------------------------------------------------------|
| Shipping Dimensions (hwd / cm)       | 11.18 x 18.80 x 50.80                                                           |
| Shipping Weight (lbs.)               | 5.20                                                                            |
| Shipping Weight (kg)                 | 2.36                                                                            |
| Unit Dimensions (hwd / in.)          | 1.710 x 16.780 x 4.770                                                          |
| Unit Packaging Type                  | Box                                                                             |
| Unit Weight (lbs.)                   | 3.50                                                                            |
| Unit Weight (kg)                     | 1.59                                                                            |
| <b>ENVIRONMENTAL</b>                 |                                                                                 |
| Operating Temperature Range          | 32° to 104°F (0° to 40°C)                                                       |
| Storage Temperature Range            | -40° to 158°F (-40° to 70°C)                                                    |
| Relative Humidity                    | 0% to 80% RH, Non-Condensing                                                    |
| BTUs                                 | 27.3 BTU/Hr                                                                     |
| <b>COMMUNICATIONS</b>                |                                                                                 |
| IP Remote Access                     | No                                                                              |
| <b>PORT EXPANSION</b>                |                                                                                 |
| Daisy-chainable or Cascadable        | Cascadeable                                                                     |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                                                                                 |
| NIAP-Certified Secure                | No                                                                              |
| Number of Users                      | 1                                                                               |
| On-Screen Display (OSD)              | Yes                                                                             |
| Port Selection                       | Pushbutton; Hotkey; OSD                                                         |
| Driver Required                      | No                                                                              |
| Recommended Category Cable           | Cat5e/6 Cables                                                                  |
| <b>STANDARDS &amp; COMPLIANCE</b>    |                                                                                 |
| Product Certifications               | CAN/CSA C22.2; CAN/CSA-C22.2 No. 60950-1 (Canada); UL 60950-1                   |
| Product Compliance                   | RoHS; CE (Europe); REACH; FCC Part 15 Class A (USA); Trade Agreements Act (TAA) |
| <b>WARRANTY &amp; SUPPORT</b>        |                                                                                 |
| Product Warranty Period (Worldwide)  | 3-year limited warranty                                                         |



*Powering Business Worldwide*



1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.