



# USB 3.0 to Gigabit Ethernet NIC Network Adapter - 10/100/1000 Mbps, White

# MODEL NUMBER: U336-000-GBW











USB 3.0 Gigabit Ethernet adapter connects your laptop to a wired Ethernet network for 10/100/1000 Mbps data transfer speeds.

#### **Features**

USB 3.0 to Gigabit Ethernet Adapter Connects You to a Wired 10/100/1000 Mbps NetworkThis USB 3.0 Gigabit Ethernet NIC network adapter instantly connects your computer, laptop, notebook, MacBook, Ultrabook or Chromebook to a 10/100/1000 Mbps network through a USB port. No internal Ethernet card is required. Just connect the built-in USB plug to your computer, and use a Cat5e/6 cable (sold separately) to connect the RJ45 end to a wired Gigabit Ethernet network. This network adapter is ideal for use in areas where Wi-Fi is unavailable or a wired connection offers faster speeds.

**Compliant with State-of-the-Art USB 3.0 Speeds**Because this Gigabit Ethernet adapter complies with USB 3.0 (5 Gbps) specifications, you are ensured true 10/100/1000 Mbps network speed without a compromise in signal quality.

Plug-and-Play Operation Lets You Begin Transferring Data Almost ImmediatelyNo external power is required. Just connect the adapter to both your computer and an RJ45 Gigabit Ethernet port for network access without the need to find an AC outlet. The lightweight unit is easy to carry in a pocket, purse, backpack or laptop bag for instant file transfers where needed. It's compatible with Windows, Mac and Linux.

Manufactured to Exacting Standards to Ensure a Full Ethernet Experience This USB 3.0 Gigabit Ethernet adapter complies with IEEE 802.3 (10Base-T), 802.3u (100Base-TX), 802.3ab and 802.3az (Energy Efficient Ethernet) standards. It supports full- and half-duplex operations, suspend mode and remote wakeup via link-up and magic packet. Diagnostic LEDs indicate when you are connected to a network and when data is being transferred.

### **Highlights**

- Connects your laptop to a Gigabit Ethernet network when Wi-Fi is unavailable
- Supports true 10/100/1000
   Mbps Ethernet network speeds for fast downloads
- USB 3.0 compatibility allows large data transfers with no compromise in signal quality
- Plug-and-play operation allows you to set it up and begin using it immediately
- Small enough to carry in a pocket or purse for fast file transfers anywhere

#### **Applications**

- Connect to a wired Gigabit Ethernet network in an office, trade show booth, lecture hall, classroom, hotel lobby or auditorium
- Extend the life of a legacy laptop or notebook computer with a failed internal Ethernet card
- Play network gaming consoles in areas without Wi-Fi capability

#### **System Requirements**

- IBM-compatible Pentium 233 MHz or faster PC or Mac
- 64 MB RAM or more
- USB-A port (USB 3.0 port required to achieve USB 3.0 speeds)
- Windows (XP through 10), Mac (10.6 through 10.12) or Linux Kernel (2.6.25 and later) operating system

## **Package Includes**

- U336-000-GBW USB 3.0 to Gigabit Ethernet NIC Network Adapter, White
- Driver CD
- · Quick Start Guide

# **Specifications**

OVERVIEW	
UPC Code	037332183286





INPUT  Bus Powered Yes  Product Length (in.) 7.5  POWER  Power Consumption (Watts) 0.5  CONNECTIONS  Side A - Connector 1 USB 3.0 A (MALE)  Side B - Connector 1 RJ45 (FEMALE)  Connector Plating Nickel  PHYSICAL  Color White  Material of Construction ABS, PVC  Cable Jacket Rating VW-1  Shipping Dimensions (hwd / in.) 0.90 x 5.20 x 5.20  Shipping Weight (lbs.) 0.14  Unit Dimensions (hwd / in.) 0.000 x 0.000 x 0.000  Unit Packaging Type Box  Unit Weight (lbs.) 0.06  Unit Weight (kg) 0.03  ENVIRONMENTAL  Operating Temperature Range 32° to 158°F (0° to 70°C)  Storage Temperature Range 14° to 176°F (-10° to 80°C)  Relative Humidity 10% to 90 % RH, Non-Condensing  BTUs			
Bus Powered Yes Product Length (in.) 7.5  POWER Power Consumption (Watts) 0.5  CONNECTIONS Side A - Connector 1 USB 3.0 A (MALE) Side B - Connector 1 RJ45 (FEMALE) Connector Plating Nickel  PHYSICAL  Color White Material of Construction ABS, PVC  Cable Jacket Rating VW-1 Shipping Dimensions (hwd / in.) 0.90 x 5.20 x 5.20 Shipping Weight (lbs.) 0.14 Unit Dimensions (hwd / in.) 0.000 x 0.000 x 0.000 Unit Packaging Type Box Unit Weight (lbs.) 0.06 Unit Weight (kg) 0.03  ENVIRONMENTAL  Operating Temperature Range 32° to 158°F (0° to 70°C) Storage Temperature Range 14° to 176°F (-10° to 80°C) Relative Humidity 10% to 90 % RH, Non-Condensing			
Product Length (in.)  POWER  Power Consumption (Watts)  Side A - Connector 1  Side B - Connector 1  Connector Plating  PHYSICAL  Color  Material of Construction  Cable Jacket Rating  Shipping Dimensions (hwd / in.)  Unit Dimensions (hwd / in.)  Unit Dimensions (hwd / in.)  Unit Packaging Type  Box  Unit Weight (lbs.)  Unit Weight (lbs.)  Unit Weight (kg)  Dono  ENVIRONMENTAL  Operating Temperature Range  14° to 176°F (-10° to 80°C)  Relative Humidity  10% to 90 % RH, Non-Condensing			
POWER  Power Consumption (Watts)  CONNECTIONS  Side A - Connector 1  Side B - Connector 1  Connector Plating  Nickel  PHYSICAL  Color  Material of Construction  ABS, PVC  Cable Jacket Rating  VW-1  Shipping Dimensions (hwd / in.)  Unit Dimensions (hwd / in.)  Unit Packaging Type  Box  Unit Weight (lbs.)  Unit Weight (kg)  ENVIRONMENTAL  Operating Temperature Range  Side A - Connector 1  USB 3.0 A (MALE)  RJ45 (FEMALE)  Nickel  White  ABS, PVC  Cable Jacket Rating  VW-1  Shipping Dimensions (hwd / in.)  0.90 x 5.20 x 5.20  Shipping Weight (lbs.)  Unit Packaging Type  Box  Unit Weight (kg)  D.06  Unit Weight (kg)  ENVIRONMENTAL  Operating Temperature Range  14° to 176°F (-10° to 80°C)  Relative Humidity  10% to 90 % RH, Non-Condensing			
Power Consumption (Watts)  CONNECTIONS  Side A - Connector 1 USB 3.0 A (MALE)  Side B - Connector 1 RJ45 (FEMALE)  Connector Plating Nickel  PHYSICAL  Color White  Material of Construction ABS, PVC  Cable Jacket Rating VW-1  Shipping Dimensions (hwd / in.) 0.90 x 5.20 x 5.20  Shipping Weight (lbs.) 0.14  Unit Dimensions (hwd / in.) 0.000 x 0.000 x 0.000  Unit Packaging Type Box  Unit Weight (lbs.) 0.06  Unit Weight (kg) 0.03  ENVIRONMENTAL  Operating Temperature Range 32° to 158°F (0° to 70°C)  Storage Temperature Range 14° to 176°F (-10° to 80°C)  Relative Humidity 10% to 90 % RH, Non-Condensing			
CONNECTIONS  Side A - Connector 1 USB 3.0 A (MALE)  Side B - Connector 1 RJ45 (FEMALE)  Connector Plating Nickel  PHYSICAL  Color White  Material of Construction ABS, PVC  Cable Jacket Rating VW-1  Shipping Dimensions (hwd / in.) 0.90 x 5.20 x 5.20  Shipping Weight (lbs.) 0.14  Unit Dimensions (hwd / in.) 0.000 x 0.000 x 0.000  Unit Packaging Type Box  Unit Weight (lbs.) 0.06  Unit Weight (kg) 0.03  ENVIRONMENTAL  Operating Temperature Range 32° to 158°F (0° to 70°C)  Storage Temperature Range 14° to 176°F (-10° to 80°C)  Relative Humidity 10% to 90 % RH, Non-Condensing			
Side A - Connector 1         USB 3.0 A (MALE)           Side B - Connector 1         RJ45 (FEMALE)           Connector Plating         Nickel           PHYSICAL           Color         White           Material of Construction         ABS, PVC           Cable Jacket Rating         VW-1           Shipping Dimensions (hwd / in.)         0.90 x 5.20 x 5.20           Shipping Weight (lbs.)         0.14           Unit Dimensions (hwd / in.)         0.000 x 0.000 x 0.000           Unit Packaging Type         Box           Unit Weight (lbs.)         0.06           Unit Weight (kg)         0.03           ENVIRONMENTAL         Operating Temperature Range         32° to 158°F (0° to 70°C)           Storage Temperature Range         14° to 176°F (-10° to 80°C)           Relative Humidity         10% to 90 % RH, Non-Condensing			
Side B - Connector 1  Connector Plating  Nickel  PHYSICAL  Color  White  Material of Construction  ABS, PVC  Cable Jacket Rating  VW-1  Shipping Dimensions (hwd / in.)  0.90 x 5.20 x 5.20  Shipping Weight (lbs.)  Unit Dimensions (hwd / in.)  Unit Packaging Type  Box  Unit Weight (lbs.)  Unit Weight (kg)  ENVIRONMENTAL  Operating Temperature Range  32° to 158°F (0° to 70°C)  Storage Temperature Range  14° to 176°F (-10° to 80°C)  Relative Humidity  RAS, PVC  0.90 x 5.20 x 5.20  Solve S.20 x 5.20  Solve			
Connector Plating  PHYSICAL  Color  White  Material of Construction  Cable Jacket Rating  VW-1  Shipping Dimensions (hwd / in.)  Shipping Weight (lbs.)  Unit Dimensions (hwd / in.)  Unit Packaging Type  Box  Unit Weight (lbs.)  Unit Weight (kg)  ENVIRONMENTAL  Operating Temperature Range  14° to 176°F (-10° to 80°C)  Relative Humidity  Nickel  White  Nickel  Nickel  Nickel  PHYSICAL  Note  ABS, PVC  0.90 x 5.20 x 5.20  S.20 x 5.20			
PHYSICAL  Color White  Material of Construction ABS, PVC  Cable Jacket Rating VW-1  Shipping Dimensions (hwd / in.) 0.90 x 5.20 x 5.20  Shipping Weight (lbs.) 0.14  Unit Dimensions (hwd / in.) 0.000 x 0.000 x 0.000  Unit Packaging Type Box  Unit Weight (lbs.) 0.06  Unit Weight (kg) 0.03  ENVIRONMENTAL  Operating Temperature Range 32° to 158°F (0° to 70°C)  Storage Temperature Range 14° to 176°F (-10° to 80°C)  Relative Humidity 10% to 90 % RH, Non-Condensing			
Color White  Material of Construction ABS, PVC  Cable Jacket Rating VW-1  Shipping Dimensions (hwd / in.) 0.90 x 5.20 x 5.20  Shipping Weight (lbs.) 0.14  Unit Dimensions (hwd / in.) 0.000 x 0.000 x 0.000  Unit Packaging Type Box  Unit Weight (lbs.) 0.06  Unit Weight (kg) 0.03  ENVIRONMENTAL  Operating Temperature Range 32° to 158°F (0° to 70°C)  Storage Temperature Range 14° to 176°F (-10° to 80°C)  Relative Humidity 10% to 90 % RH, Non-Condensing			
Material of Construction  Cable Jacket Rating  VW-1  Shipping Dimensions (hwd / in.)  Shipping Weight (lbs.)  Unit Dimensions (hwd / in.)  Unit Packaging Type  Box  Unit Weight (lbs.)  Unit Weight (kg)  ENVIRONMENTAL  Operating Temperature Range  32° to 158°F (0° to 70°C)  Storage Temperature Range  14° to 176°F (-10° to 80°C)  Relative Humidity  ABS, PVC  VW-1  300 ABS, PVC  0.90 × 5.20 × 5.20  0.000  0.000 × 0.000 × 0.000  0.000 × 0.000  0.000 × 0.000  0.000 × 0.000  10° to 70°C)  10° to 70°C)			
Cable Jacket Rating  VW-1  Shipping Dimensions (hwd / in.)  Shipping Weight (lbs.)  Unit Dimensions (hwd / in.)  Unit Packaging Type  Box  Unit Weight (lbs.)  Unit Weight (kg)  ENVIRONMENTAL  Operating Temperature Range  32° to 158°F (0° to 70°C)  Storage Temperature Range  14° to 176°F (-10° to 80°C)  Relative Humidity  VW-1  0.90 x 5.20 x 5.20  0.000  0.014  0.000 x 0.000 x 0.000  0.000  0.000 x 0.000  0.000  1000 x			
Shipping Dimensions (hwd / in.)  Shipping Weight (lbs.)  Unit Dimensions (hwd / in.)  Unit Packaging Type  Box  Unit Weight (lbs.)  Unit Weight (kg)  ENVIRONMENTAL  Operating Temperature Range  32° to 158°F (0° to 70°C)  Storage Temperature Range  14° to 176°F (-10° to 80°C)  Relative Humidity  10% to 90 % RH, Non-Condensing			
Shipping Weight (lbs.)  Unit Dimensions (hwd / in.)  Unit Packaging Type  Box  Unit Weight (lbs.)  Unit Weight (kg)  ENVIRONMENTAL  Operating Temperature Range  32° to 158°F (0° to 70°C)  Storage Temperature Range  14° to 176°F (-10° to 80°C)  Relative Humidity  10% to 90 % RH, Non-Condensing			
Unit Dimensions (hwd / in.)  Unit Packaging Type  Box  Unit Weight (lbs.)  Unit Weight (kg)  ENVIRONMENTAL  Operating Temperature Range  32° to 158°F (0° to 70°C)  Storage Temperature Range  14° to 176°F (-10° to 80°C)  Relative Humidity  10% to 90 % RH, Non-Condensing			
Unit Packaging Type  Unit Weight (lbs.)  Unit Weight (kg)  ENVIRONMENTAL  Operating Temperature Range  32° to 158°F (0° to 70°C)  Storage Temperature Range  14° to 176°F (-10° to 80°C)  Relative Humidity  10% to 90 % RH, Non-Condensing			
Unit Weight (lbs.)  Unit Weight (kg)  0.03  ENVIRONMENTAL  Operating Temperature Range  32° to 158°F (0° to 70°C)  Storage Temperature Range  14° to 176°F (-10° to 80°C)  Relative Humidity  10% to 90 % RH, Non-Condensing			
Unit Weight (kg)  ENVIRONMENTAL  Operating Temperature Range  32° to 158°F (0° to 70°C)  Storage Temperature Range  14° to 176°F (-10° to 80°C)  Relative Humidity  10% to 90 % RH, Non-Condensing			
ENVIRONMENTAL  Operating Temperature Range 32° to 158°F (0° to 70°C)  Storage Temperature Range 14° to 176°F (-10° to 80°C)  Relative Humidity 10% to 90 % RH, Non-Condensing			
Operating Temperature Range 32° to 158°F (0° to 70°C)  Storage Temperature Range 14° to 176°F (-10° to 80°C)  Relative Humidity 10% to 90 % RH, Non-Condensing			
Operating Temperature Range 32° to 158°F (0° to 70°C)  Storage Temperature Range 14° to 176°F (-10° to 80°C)  Relative Humidity 10% to 90 % RH, Non-Condensing	ENVIRONMENTAL		
Storage Temperature Range 14° to 176°F (-10° to 80°C)  Relative Humidity 10% to 90 % RH, Non-Condensing			
Relative Humidity 10% to 90 % RH, Non-Condensing			
L L			
COMMUNICATIONS			
Network Compatibility 1 Gbps (Gigabit)			
IEEE Standards Supported 802.3; 802.3ab; 802.3az; 802.3u; 802.3x			
FEATURES & SPECIFICATIONS			
USB Specification USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (u			
Auto MDIX Support Yes	o 5 Gbps)		
Full Duplex Support Yes	o 5 Gbps)		





Suspend Mode Support	Yes	
Remote Wakeup Support	Yes	
Driver Required	Yes	
Recommended Category Cable	Cat5/Cat5e/Cat6 Cables	
STANDARDS & COMPLIANCE		
Product Compliance	RoHS; CE (Europe); REACH; FCC (USA)	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	3-year limited warranty	

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2024 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.